



## TYS-031C/TYH-032C SERIES

Soft / Hard Winder ( Cone- Cone )

公式/紧式络筒机 ( 筒纱-筒纱 )



项目 Item	技术参数 Technical Parameters
机械速度 Mechanical speed	1200m/min(工艺参数决定工艺速度) Up to 1200m/min(depending on yarn quality and count)
防叠方式 Way of anti-overlapping	变频防叠 Frequency conversion
卷装筒管 Package bobbin	0°,3°30'
卷装直径 Package diameter	可达φ290mm ; Up toφ290 mm
卷装重量 Package weight	可达3kg Up to 3kg
适纺原料/支数 Yarns /count	棉,麻,毛,丝,化纤Ne6-180 Cotton,flax,wool,silk,chemical fiber/Ne 6...180
单锭功率 Power consumption	装机100W,消耗65W; Installed power:100W/spindle,Power consumption:65W/spindle
断纱自停 Auto stop while yarn break	电子断纱自停 With electronic yarn detector,the spindle will stop when yarn break
电子定长 Automatic length fixing	自动定长,最长999999m Automatic length fixing,max:999999m
整机慢启动 Slow start	保证平稳启动提高卷绕质量,支持单锭慢启动(可选配) For smooth start and better winding quality,supporting individual slow start for each spindle(available on request)
电子清纱器 Electronic yarn clearer	可选配 Optional
空气捻接器 Air splicer	可选配 Optional
巡回吹吸风 Travelling blower/suction unit	可选配,功率1.1KW Optional, power consumption 1.1KW
上输送/中间输送/下尾管输送 Conveyor	可选配 Optional
外形尺寸(2180mm/节) External dimensions	2180mm×N+380mm
每节质量 Weight of each section	270kg
电源 Power supply	三相380V±10%,50/60HZ 3phased 380V±10%,50/60HZ

\*敝司保留技术最后之修改权利而不再另行通知。

\*We reserve our rights to change the specification without prior notice.

## CTH-033C SERIES

Reeling Machine ( Cone-Hank )

摇纱机 ( 筒纱-绞纱 )



型号 Model	CTH-033C
描述 Description	筒纱倒绞纱 Cone to hank
形式 Type	单面上框,下入式 Single side
绞数 NO. of hank	24
绞距 Distance between hank	100-140mm
转速 Speed	300-350rpm
绞纱框 Hank frame	6杆支撑 6 bar support
功率 Power	0.55KW



## HTC-035C SERIES

Hank To Cone Winder

公式/紧式络筒机 ( 绞纱-筒纱 )



型号 Model	HTC-035C
描述 Description	绞纱倒筒纱 Hank to cone
机械速度 Machine speed	Max.300m/min
防叠方式 Way of anti-overlapping	变频防叠 Frequency conversion
卷装筒管 Package bobbin	0°, 3°30'
卷装直径 Dia. of package	Max.Dia. 290mm
卷装重量 Weight of package	Max.3KG
单锭功率 Power /per spindle	装机功率100W,消耗功率65W ; Installed power 100W, Consumption power 65W
断纱自停 Auto break	标配 Yes
电子定长 Auto length fixing	标配 Yes ( Max.999999m)
整机慢启动 Slow start	标配 Yes
电源 Power	三相电 three phrase 380V+/-10%,50/60Hz