

SH SERIES

Normal Pressure Spray Type Hank Dyeing Machine

绞纱染色机

SH系列喷射式常温绞纱染色机广泛应用于天然纤维纱线(棉,麻,丝,羊毛等),合成纤维纱线(涤纶,锦纶,腈纶等),混纺纤维纱线(天然纤维和合成纤维混纺而成)。特别适用于染光丝、真丝、人造丝、绢丝、单股细纱、丝光棉及其混纺等绞纱。这些纱线在服装、家纺、装饰布艺等领域有着广泛的应用。

SH Series normal temperature spray hank dyeing machine is widely used in dyeing natural fiber yarn(cotton, linen, silk, wool, etc.) synthetic fiber yarn (polyester, nylon, acrylic, etc.) and blended fiber yarn. It is particularly suitable for dyeing spun silk, pure silk, artificial silk, single-strand fine yarn, mercerized cotton yarn and their blends. These yarn with extensive application in apparel, home textile, decorative fabric and other sectors.



无锡新统运机械科技有限公司

WUXI SHIN TONG YUNN MACHINERY TECHNOLOGY CO.,LTD.

<http://www.yarnfabricdyeingmachine.com>



SH-1X4-20



SH-10-150



SH-1-65



SH-20-150

技术规格 SPECIFICATIONS

型号 Model	载量 Capacity (KG)	喷管数 Number of spray pipe	主功率 Main Power (KW)	外型尺寸 Dimensions		
				L(mm)	W(mm)	H(mm)
SH-1-65	3	1	1.1	1050	1950	2020
SH-2-65	7	2	1.1	1325	1950	2020
SH-2-120	14	2	1.5	1325	2150	2500
SH-4-120	28	4	3	2000	2150	2500
SH-6-120	42	6	4	2500	2200	2500
SH-10-150	100	10	5.5	3750	2960	2650
SH-20-150	200	20	11	6000	3150	2700
SH-30-150	300	30	18.5	9000	3250	2700
SH-40-150	400	40	22	11800	3250	2700
SH-50-150	500	50	30	14300	3250	2750
SH-60-150	600	60	30	17500	3300	2750
SH-80-150	800	80	37	22800	3300	2750
SH-100-150	1000	100	45	28500	3300	2750
SH-30X2-150	600	60	37	9000	7000	2700
SH-40X2-150	800	80	44	11800	7000	2700
SH-50X2-150	1000	120	60	14300	7000	2750
SH-60X2-150	1200	160	60	17500	7000	2750
SH-80X2-150	1600	160	74	22800	7000	2750
SH-100X2-150	2000	200	90	28500	7000	2750